Listing of Claims

This listing of claims will replace all prior versions of claims and listings of claims in the application:

- 1. (Previously Presented) A monitoring system for distributed utilities, the monitoring system comprising:
- a. a water purification device for converting available water to purified water, the water purification device characterized by a plurality of operating parameters;
- b. an input sensor for measuring source water entering the water purification device:
- c. an output flow rate sensor for measuring the amount of purified water leaving the water purification device;
- d. a local controller for concatenating the measured source water entering the amount of purified water leaving on the basis of the input and output sensors; and
- e. a remote controller for modifying operation of the water purification device based on the concatenated measured source water entering and the amount of-purified water leaving.
- 2. (Previously Presented) A monitoring system according to claim 1, further comprising at least one sensor for measuring at least one parameter of the plurality of operating parameters of the water purification device.
- 3. (Previously Presented) A monitoring system according to claim 2, wherein the at least one sensor is a heat transfer monitor.
- 4. (Previously Presented) A monitoring system according to claim 2, wherein the at least one sensor is a flow impedance monitor.
 - 5. (Cancelled)

Appl. No. 10/566,307 Amdt. Dated August 26, 2010 Reply to Office Action of February 26, 2010

6. (Previously Presented) A monitoring system according to claim 1, wherein the input sensor is a flow rate monitor.

7. (Previously Presented) A monitoring system according to claim 6, wherein the output flow rate sensor includes a water quality sensor including at least one of a turbidity, conductivity,

and temperature sensor.

8. (Previously Presented) A monitoring system according to claim 7, further comprising a shut off switch that automatically turns off the water purification device when the water quality

sensor rises above a pre-programmed water quality value.

9. (Previously Presented) A monitoring system according to claim 7, further comprising

an alarm that alerts a user when the water quality value rises above a pre-programmed water

quality value.

10. (Original) A monitoring system according to claim 7, further comprising a remotely

operable shut off switch.

11. (Cancelled)

12. (Cancelled)

13. (Cancelled)

14. (Original) A monitoring system according to claim 1, further comprising a telemetry

module for communicating measured input and output parameters to a remote site.

15. (Original) A monitoring system according to claim 14, wherein the telemetry module

is a cellular communications system.

Page 3 of 10

Appl. No. 10/566,307 Amdt. Dated August 26, 2010 Reply to Office Action of February 26, 2010

- 16. (Original) A monitoring system according to claim 14, wherein the telemetry module is a wireless system.
- 17. (Previously Presented) A monitoring system according to claim 1, further including a remote actuator for varying operating parameters of the water purification based on remotely received instructions.
- 18. (Original) A monitoring system according to claim 1, further including a self-locating device having an output indicative of the location of the monitoring system.
- 19. (Original) A monitoring system according to claim 18, wherein the self-locating device is a global positioning system.
- 20. (Original) A monitoring system according to claim 18, wherein monitored characteristics of input and output depend upon the location of the monitoring system.
 - 21. (Previously Presented) A method for assembling a monitoring system comprising:
 - a. providing a water purification device;
- b. coupling an input sensor for measuring source water entering the water purification device;
- c. coupling an output sensor for measuring the amount of purified water leaving the water purification device;
- d. coupling a local controller to the input and output sensor for concatenating the measured source water entering and the amount of purified water leaving on the basis of the input and output sensors; and
- e. providing a remote controller for modifying operation of the water purification device based on the concatenated measured source water entering and the amount of purified water leaving.
 - 22. (Previously Presented) The method of claim 21, further comprising:

Appl. No. 10/566,307 Amdt. Dated August 26, 2010 Reply to Office Action of February 26, 2010

- a. providing communication between a telemetry module and the controller; and
- b. providing communication between the telemetry module and a monitoring station.
 - 23. (Previously Presented) A distributed network of utilities, comprising:
- a. at least one water purification device for converting source water to purified water;
- b. input sensors for measuring source water entering the at least one water purification device;
- c. output sensors for measuring the amount of purified water leaving the at least one water purification device, wherein the at least one water purification device has a local controller that concatenates the measured source water entering and the amount of purified water leaving the at least one water purification device;
- d. a telemetry transmitter for transmitting input and output parameters of the at least one water purification device; and
- e. a remote controller for receiving the concatenated source water entering and the amount of purified water leaving from the at least one water purification device and modifying operation of the at least one water purification device based on the concatenated source water entering and the amount of purified water leaving.

24. (Cancelled)